

AD-A082 967 ARMY ELECTRONICS RESEARCH AND DEVELOPMENT COMMAND WS--ETC F/6 4/2  
193088 MLRS, MISSILE NUMBER 1091, ROUND NUMBER V-96, 8 DECEMBER--ETC(U)  
DEC 79


UNCLASSIFIED ERADCOM/ASL-DR-1101

NL

OP  
AD-A082 967



END  
DATE  
FILMED  
5-80  
DTIC



## **DISCLAIMER NOTICE**

**THIS DOCUMENT IS BEST QUALITY  
PRACTICABLE. THE COPY FURNISHED  
TO DTIC CONTAINED A SIGNIFICANT  
NUMBER OF PAGES WHICH DO NOT  
REPRODUCE LEGIBLY.**

14 EMDOC 1/11 SL-DR-1191

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 1101-DR	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) 193088 MLRS Missile Number 1091, Round Number V-96		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) 9 White Sands Meteorological Team		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS White Sands Meteorological Team		8. CONTRACT OR GRANT NUMBER(s) 16 DA Task 1F665702D127-02
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Electronics Research & Development Cmd Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico 88002		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 14 17 22
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) US Army Electronics Research & Development Cmd Adelphi, MD 20783		12. REPORT DATE December 1979
		13. NUMBER OF PAGES 14 12 15
		15. SECURITY CLASS. (of this Report) UNCLASSIFIED
16. DISTRIBUTION STATEMENT (of this Report)		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) Approved for public release; distribution unlimited.		Accession For NTIS GRA&I <input checked="" type="checkbox"/> DDC TAB <input type="checkbox"/> Unannounced <input type="checkbox"/> Justification <input type="checkbox"/>
18. SUPPLEMENTARY NOTES		By Distribution/ Availability Codes
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		Dist A 23 OP
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Meteorological data gathered for the launching of the 193088 MLRS, Missile Number 1091, Round Number V-96 are presented in tabular form.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

4100-

JOP

## CONTENTS

	PAGE
INTRODUCTION-----	1
DISCUSSION-----	1
TABLES:	
1. Surface Observations taken at 0845 MST at D 3½-----	2
2. D 3½ Pilot Balloon Measured Wind Data at 0845 MST-----	3
3. DENVER Pilot Balloon Measured Wind Data at 0845 MST-----	4
4. NW30 Significant Level Data at 0830 MST-----	5
5. NW30 Upper Air Data at 0830 MST-----	6
6. NW30 Mandatory Levels at 0830 MST-----	10

## INTRODUCTION

19308B MLRS, Missile Number 1091, Round Number V-96,  
was launched from BRILLO, White Sands Missile Range (WSMR), New Mexico,  
at 0844:06 MST on 08 December 1979. The scheduled launch time was  
0830 MST.

## DISCUSSION

Meteorological data were recorded and reduced by the White Sands Meteorological Team, Atmospheric Sciences Laboratory (ASL), White Sands Missile Range, New Mexico. The data were obtained by the following methods:

### 1. Observations

#### a. Surface

(1) Standard surface observations to include pressure, temperature ( $^{\circ}\text{C}$ ), relative humidity, dew point ( $^{\circ}\text{C}$ ), density ( $\text{gm}/\text{m}^3$ ), Wind direction and speed, and cloud cover were made at the D 3 $\frac{1}{2}$  Met Site at T-0 minutes.

(2) Anemometer data were provided from existing pole-mounted and tower-mounted anemometers at LC-33. Monitor of wind speed and direction from one anemometer was also provided in the launch control room.

#### b. Upper Air

(1) Low level wind data were obtained from RAPTS T-9 pibal observation at:

## SITE AND ALTITUDE

D 3 $\frac{1}{2}$  2km  
DENVER 2km

(2) Air structure data (rawinsonde) were collected at the following Met Sites. Data were collected from surface to 69,500 feet in 500-foot increments.

## SITE AND TIME

NW30 0830 MST

TABLE 1 Surface Observations taken at 0845 MST,  
08 December 1979, at D 3½, 19308B MLRS,  
Missile No. 1091, Round No. V-96

ELEVATION	3975.	FT/MSL
PRESSURE	887.3	MBS
TEMPERATURE	3.9	°C
RELATIVE HUMIDITY	49	%
DEW POINT	-5.7	°C
DENSITY	1112	GM/M <sup>3</sup>
WIND SPEED	02	KTS
WIND DIRECTION	360	DEGREES
CLOUD COVER	2	CI

## PILOT BALLOON MEASURED WIND DATA

TABLE 2

RELEASED FROM D 31 DATE 08 December 1979 TIME 0845 MST

TRACKER      COORDINATES (WSTM)    X= 443,018.90      Y= 338,189.24      H 3974.89

NOTE: WIND DIRECTIONS ARE REFERENCED TO TRUE NORTH.

HEIGHTS ARE METERS AGL XX OR FEET AGL \_\_\_\_\_.[illegible][illegible][illegible]



## PILOT BALLOON MEASURED WIND DATA

TABLE 3

RELEASED FROM DENVER SITE      DATE 08 December 1979      TIME 0845 MST

TRACKER      COORDINATES (WSTM)      X= 499,064.03      Y= 493,904.12      Z= 4123.10

NOTE: WIND DIRECTIONS ARE REFERENCED TO TRUE NORTH.

HEIGHTS ARE METERS AGL XX OR FEET AGL .

[illegible][illegible][illegible]

STATION ALTITUDE 4010.40 FEET MSL  
8 DEC. 79 0830 HRS MST  
ASCENSION NO. 14

SIGNIFICANT LEVEL DATA  
3420220014  
NW 30

GEODETIC COORDINATES  
32.88497 LAT DEG  
106.49714 LON DEG

TABLE 4

PRESSURE GEOMETRIC ALTITUDE MILLIBARS MSL FEET	TEMPERATURE		REL. HUM. PERCENT
	AIR DEGREES	DEWPOINT CENTIGRADE	
297.1	4.5	-5.3	49.0
878.4	3.3	-6.4	49.0
868.4	6.5	-4.0	47.0
850.0	9.1	-2.5	44.0
819.2	8.4	-4.1	41.0
799.4	9.1	-4.4	38.0
770.8	8.1	-5.0	39.0
700.0	3.0	-9.0	39.0
660.0	1.5	-13.4	32.0
651.0	1.0	-7.5	53.0
633.4	-6	-12.8	39.0
616.2	-1.5	-11.6	46.0
573.8	-5.0	-17.1	38.0
541.0	-7.6	-20.0	36.0
500.0	-12.6	-25.0	32.0
478.0	-14.1	-27.5	31.0
400.0	-25.1	-37.2	31.0
314.2	-39.2	-49.8	31.0
300.0	-42.2		
273.8	-47.6		
250.0	-51.8		
231.4	-55.5		
212.0	-57.0		
209.0	-58.9		
156.2	-61.6		
150.0	-61.5		
137.6	-62.5		
130.6	-62.3		
120.4	-67.3		
100.0	-64.0		
97.2	-67.4		
70.0	-63.2		
60.8	-63.0		
50.0	-62.4		
46.0			

UPPER AIR DATA  
3420220014  
1.00 30

STATION ALTITUDE 4010.40 FEET MSL  
8 DEC. 79 0530 HRS MST  
ASCENSION 1.0. 14

GEODETIC COORDINATES  
32.80497 LAT DEG  
106.44714 LONG DEG

TABLE 5

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CELSIUS	REL. HUM. PERCENT	DENSITY G/CM <sup>3</sup>	SPEED OF SOUND M/SEC	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
4010.4	887.1	4.5	49.0	1111.1	649.7	325.0	4.1	1.000268
4500.0	871.0	5.7	47.5	1096.2	651.1	263.1	1.1	1.000263
5000.0	855.0	6.4	44.8	1075.7	654.4	176.0	2.9	1.000259
5500.0	839.4	6.9	43.0	1054.7	654.9	166.2	6.2	1.000254
5800.0	824.1	6.5	41.5	1037.1	654.5	163.5	8.2	1.000249
6300.0	809.1	8.0	39.5	997.6	654.8	165.0	7.8	1.000244
7100.0	794.4	6.4	38.2	973.0	655.0	203.6	8.1	1.000239
7500.0	779.9	6.4	36.7	962.9	654.4	232.1	9.7	1.000235
8000.0	765.6	7.7	39.0	947.6	653.6	239.5	11.1	1.000221
8500.0	751.5	6.8	39.0	933.5	652.4	242.7	12.2	1.000227
9000.0	737.6	5.8	39.0	919.6	651.2	248.5	10.6	1.000222
9500.0	724.0	4.8	39.0	905.9	650.1	254.5	10.0	1.000218
10000.0	710.7	3.8	39.0	892.4	648.9	258.4	10.2	1.000214
10500.0	697.5	2.9	38.6	878.8	647.8	260.3	11.4	1.000210
11000.0	684.5	2.4	36.3	864.1	647.2	261.0	13.1	1.000206
11500.0	671.7	1.9	34.1	849.5	646.6	262.6	13.9	1.000201
12000.0	659.2	1.5	33.8	835.2	646.0	262.2	14.5	1.000198
12500.0	646.9	.6	49.7	821.6	645.2	250.0	14.4	1.000199
13000.0	634.7	-.5	40.0	809.8	643.8	250.1	14.7	1.000192
13500.0	622.7	-1.2	43.5	796.4	643.0	244.7	15.4	1.000190
14000.0	610.9	-1.9	45.0	783.5	642.1	244.6	15.6	1.000187
14500.0	599.5	-2.9	42.9	771.4	640.9	240.2	15.8	1.000183
15000.0	587.9	-3.8	40.7	759.5	639.7	250.3	15.7	1.000179
15500.0	576.7	-4.8	38.0	747.7	638.6	254.1	15.9	1.000175
16000.0	565.6	-5.5	37.5	735.8	637.5	256.7	16.9	1.000172
16500.0	554.7	-6.5	36.9	724.0	636.5	253.5	17.6	1.000169
17000.0	544.1	-7.4	36.2	712.4	635.4	259.6	18.2	1.000166
17500.0	533.5	-8.5	35.3	701.6	634.0	261.5	18.5	1.000162
18000.0	523.1	-9.7	34.5	691.3	632.5	263.7	18.7	1.000159
18500.0	512.8	-11.0	33.5	681.0	631.0	264.9	18.9	1.000157
19000.0	502.8	-12.2	32.5	671.0	629.5	260.0	18.5	1.000154
19500.0	492.9	-13.1	31.7	659.9	628.4	267.5	15.3	1.000151
20000.0	483.2	-13.7	31.2	648.5	627.6	270.6	12.0	1.000148
20500.0	473.5	-14.7	31.0	637.9	626.5	260.9	8.7	1.000146
21000.0	463.9	-15.9	31.0	628.1	624.9	256.7	7.5	1.000143
21500.0	454.5	-17.2	31.0	618.4	623.4	306.0	8.4	1.000141
22000.0	445.5	-18.5	31.0	608.9	621.8	317.5	9.4	1.000138
22500.0	436.5	-19.7	31.0	599.6	620.3	324.0	10.5	1.000136
23000.0	427.5	-21.0	31.0	590.4	618.7	323.5	10.9	1.000134
23500.0	418.6	-22.5	31.0	581.4	617.2	321.6	11.0	1.000131

STATION ALTITUDE 4010.40 FEET MSL  
 H. VEL. 79  
 ASCENSION NO. 14

UPPER AIR LAT.  
 3420220014  
 TIM 30

GEODETIC COORDINATES  
 32.00497 LAT DEG  
 106.49714 LONG DEG

TABLE 5 (CONT)

GEODETIC ALTITUDE FT	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES C	REL. HUM. PERCENT	DENSITY GM/CM <sup>3</sup>	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	SPEED KNOTS	INDEX OF REFRACTION
24000.0	410.5	-25.5	31.0	572.5	615.6	315.1	11.5	1.000129
24500.0	402.0	-24.8	31.0	563.8	614.0	309.0	12.1	1.000127
25000.0	393.0	-20.0	31.0	554.7	612.5	303.0	12.7	1.000125
25500.0	385.2	-27.5	31.0	545.7	610.9	297.5	13.6	1.000123
26000.0	377.0	-28.6	31.0	536.8	609.5	292.1	14.8	1.000121
26500.0	369.0	-29.8	31.0	528.1	607.8	292.9	15.5	1.000119
27000.0	361.1	-31.1	31.0	519.6	606.2	297.0	15.9	1.000117
27500.0	353.4	-32.5	31.0	511.2	604.6	301.0	15.5	1.000115
28000.0	345.9	-33.0	31.0	502.9	603.0	307.5	14.9	1.000113
28500.0	338.5	-34.0	31.0	494.8	601.4	309.1	14.6	1.000111
29000.0	331.5	-36.1	31.0	486.9	599.8	310.7	14.3	1.000109
29500.0	324.5	-37.3	31.0	479.0	598.2	312.0	14.4	1.000107
30000.0	317.4	-38.5	31.0	471.4	596.6	315.5	14.6	1.000105
30500.0	310.5	-40.0	23.0**	463.8	594.9	310.1	14.9	1.000104
31000.0	303.6	-41.4	8.1**	456.4	593.0	318.5	15.0	1.000102
31500.0	296.9	-42.8		449.1	591.2	320.7	14.7	1.000100
32000.0	290.2	-44.2		441.6	589.4	321.6	14.1	1.000098
32500.0	283.7	-45.6		434.4	587.6	320.7	13.0	1.000097
33000.0	277.5	-47.0		427.2	585.8	319.5	12.5	1.000095
33500.0	271.0	-48.2		419.8	584.2	317.6	12.8	1.000094
34000.0	264.8	-49.5		412.0	582.9	317.4	13.9	1.000092
34500.0	258.7	-50.5		404.4	581.6	317.6	15.6	1.000090
35000.0	252.6	-51.5		397.0	580.2	315.5	15.8	1.000088
35500.0	246.9	-52.4		389.7	578.8	311.7	15.4	1.000087
36000.0	241.2	-53.5		382.5	577.4	301.7	14.0	1.000085
36500.0	235.0	-54.0		375.6	575.9	283.2	13.0	1.000084
37000.0	230.0	-55.6		368.4	574.6	273.4	16.5	1.000082
37500.0	224.8	-56.0		360.5	574.1	264.4	21.3	1.000080
38000.0	219.5	-56.4		352.5	573.5	260.2	25.1	1.000079
38500.0	214.1	-56.8		344.8	573.0	263.5	28.8	1.000077
39000.0	209.1	-57.5		337.6	572.2	272.5	30.2	1.000075
39500.0	204.1	-58.2		330.8	571.1	270.2	31.5	1.000074
40000.0	199.2	-58.9		324.0	570.2	270.4	33.2	1.000072
40500.0	194.4	-59.2		316.6	569.8	270.4	34.6	1.000071
41000.0	189.8	-59.5		309.4	569.5	270.1	35.5	1.000069
41500.0	185.2	-59.7		302.3	569.1	275.7	36.0	1.000067
42000.0	180.7	-60.0		295.4	568.8	274.8	36.1	1.000066
42500.0	176.4	-60.5		288.7	568.4	274.2	36.1	1.000064
43000.0	172.2	-60.5		282.1	568.1	274.2	36.3	1.000063
43500.0	168.0	-60.5		275.6	567.7	275.9	36.0	1.000061

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 4010.00 FEET MSL  
 8 Oct. 79 0830 MDT MST  
 ASCENDING 40. 14

UPPER AIR DATA  
 3420220014  
 00 30

GEODETIC COORDINATES  
 32.86497 LAT DEG  
 106.49714 LON DEG

TABLE 5 (CONT)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GRAMS/CUBIC METER	SPEED OF SOUND M/CTS	WIND DATA		INDEX OF REFRACTION
						DIRECTION DEGREES (TN)	SPEED KNOTS	
44500.0	164.0	-61.1		269.4	567.3	273.5	35.0	1.000060
44500.0	160.0	-61.3		262.2	567.0	273.1	33.6	1.000059
44500.0	156.2	-61.6		257.2	566.6	272.9	32.0	1.000057
44500.0	152.4	-61.5		250.9	566.7	272.5	31.7	1.000056
44500.0	148.7	-61.5		244.8	566.8	272.0	32.5	1.000055
44500.0	145.1	-61.5		238.4	566.8	270.6	31.4	1.000053
47500.0	141.6	-61.5		233.1	566.8	267.9	28.6	1.000052
47500.0	136.2	-61.5		227.5	566.8	265.6	26.2	1.000051
46000.0	134.9	-61.9		222.4	566.3	265.0	24.5	1.000050
46500.0	131.6	-62.4		217.5	565.8	263.9	23.3	1.000048
47000.0	126.4	-62.5		212.3	565.5	262.6	23.2	1.000047
49500.0	125.3	-62.4		207.1	565.6	260.4	22.8	1.000046
52000.0	122.3	-62.3		202.0	565.6	255.9	21.4	1.000045
50500.0	119.3	-62.6		197.3	565.4	251.9	20.8	1.000044
51000.0	116.4	-63.2		193.1	564.5	250.4	21.8	1.000043
51500.0	113.5	-63.9		188.9	563.6	249.6	22.6	1.000042
52000.0	110.7	-64.5		184.9	562.7	250.4	23.0	1.000041
52500.0	108.0	-65.2		180.9	561.8	251.2	23.2	1.000040
53000.0	105.3	-65.9		177.1	560.8	252.2	22.2	1.000039
53500.0	102.6	-66.5		173.3	559.9	253.4	21.2	1.000039
54000.0	100.2	-67.2		169.6	559.0	252.1	20.2	1.000038
54500.0	97.8	-68.3		165.0	559.7	250.5	19.2	1.000037
55000.0	95.4	-68.2		160.3	560.5	250.3	18.3	1.000036
55500.0	93.0	-65.5		156.1	561.3	250.2	17.5	1.000035
56000.0	90.7	-65.0		151.8	562.1	249.4	16.4	1.000034
56500.0	88.3	-64.4		147.6	562.9	248.1	15.1	1.000033
57000.0	86.3	-64.2		143.9	563.2	248.9	14.5	1.000032
57500.0	84.2	-64.5		140.6	562.7	251.2	14.2	1.000031
58000.0	82.1	-64.9		137.4	562.2	257.5	13.8	1.000031
58500.0	80.1	-65.3		134.3	561.6	271.1	13.6	1.000030
59000.0	78.1	-65.7		131.2	561.1	284.1	14.0	1.000029
59500.0	76.2	-66.1		128.2	560.6	296.7	13.2	1.000029
60000.0	74.3	-66.5		125.3	560.1	310.3	13.0	1.000028
60500.0	72.3	-66.9		122.4	559.5	310.9	11.2	1.000027
61000.0	70.7	-67.2		119.6	559.0	308.1	9.0	1.000027
61500.0	69.0	-67.0		116.5	559.4	295.8	6.8	1.000026
62000.0	67.3	-66.2		113.3	560.4	284.6	5.6	1.000025
62500.0	65.6	-65.5		110.1	561.4	253.3	6.8	1.000025
63000.0	64.0	-64.7		107.0	562.4	214.7	8.4	1.000024
63500.0	62.4	-64.9		104.0	563.4	202.9	10.6	1.000023

STATION ALTITUDE 4010.40 FEET MSL  
8 DEC. 79 0830 HRS MST  
ASCENSION NO. 14

UPPER AIR DATA  
3420220014  
NW 30

GEODETIC COORDINATES  
32.86497 LAT DEG  
106.49714 LON DEG

TABLE 5 (CONT)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CM <sup>3</sup> METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
							DIRECTION DEGREES (TN)	SPEED KNOTS	
44000.0	164.0	-61.1			269.4	567.3	273.5	35.0	1.000060
44500.0	160.0	-61.3			263.2	567.0	273.1	33.6	1.000059
45000.0	156.2	-61.6			257.2	566.6	272.9	32.0	1.000057
45500.0	152.4	-61.5			250.9	566.7	272.5	31.7	1.000056
46000.0	148.7	-61.5			244.8	566.8	272.0	32.5	1.000055
46500.0	145.1	-61.5			238.9	566.8	270.6	31.4	1.000053
47000.0	141.6	-61.5			233.1	566.8	267.9	28.6	1.000052
47500.0	138.2	-61.5			227.5	566.8	265.8	26.2	1.000051
48000.0	134.9	-61.9			222.4	566.3	263.0	24.5	1.000050
48500.0	131.6	-62.4			217.5	565.6	263.9	23.3	1.000048
49000.0	128.4	-62.5			212.3	565.5	262.6	23.2	1.000047
49500.0	125.3	-62.4			207.1	565.6	260.4	22.8	1.000046
50000.0	122.3	-62.3			202.0	565.6	255.9	21.4	1.000045
50500.0	119.3	-62.6			197.3	565.4	251.9	20.8	1.000044
51000.0	116.4	-63.2			193.1	564.5	250.4	21.8	1.000043
51500.0	113.5	-63.9			188.9	563.6	249.6	22.6	1.000042
52000.0	110.7	-64.6			184.9	562.7	250.4	23.0	1.000041
52500.0	108.0	-65.2			180.9	561.8	251.2	23.2	1.000040
53000.0	105.3	-65.9			177.1	560.8	252.2	22.2	1.000039
53500.0	102.8	-66.5			173.3	559.9	253.4	21.2	1.000039
54000.0	100.2	-67.2			169.6	559.0	252.1	20.2	1.000038
54500.0	97.8	-68.3			165.0	559.7	250.5	19.2	1.000037
55000.0	95.4	-68.2			160.5	560.5	251.3	18.3	1.000036
55500.0	93.0	-65.6			156.1	561.3	250.2	17.5	1.000035
56000.0	90.7	-65.0			151.8	562.1	249.4	16.4	1.000034
56500.0	88.5	-64.4			147.6	562.9	248.1	15.1	1.000033
57000.0	86.3	-64.2			143.9	563.2	248.9	14.5	1.000032
57500.0	84.2	-64.5			140.6	562.7	251.2	14.2	1.000031
58000.0	82.1	-64.9			137.4	562.2	257.5	13.8	1.000031
58500.0	80.1	-65.3			134.3	561.6	271.1	13.6	1.000030
59000.0	78.1	-65.7			131.2	561.1	264.1	14.0	1.000029
59500.0	76.2	-66.1			128.2	560.6	253.7	13.2	1.000029
60000.0	74.3	-66.5			125.3	560.1	310.3	13.0	1.000028
60500.0	72.3	-66.9			122.4	559.5	310.9	11.2	1.000027
61000.0	70.7	-67.2			119.6	559.0	308.1	9.0	1.000027
61500.0	69.0	-67.0			116.5	559.4	293.8	6.8	1.000026
62000.0	67.3	-66.2			113.3	560.4	264.6	5.6	1.000025
62500.0	65.0	-65.5			110.1	561.4	233.3	6.8	1.000025
63000.0	64.0	-64.7			107.0	562.4	214.7	8.4	1.000024
63500.0	62.4	-64.0			104.0	563.4	202.9	10.6	1.000023

UPPER AIR DATA  
3420220014  
IN 40

STATION ALTITUDE 401.00 FEET ASL  
3420220014  
IN 40

GEOMETRIC COORDINATES  
34.00497 LAT NRG  
106.49714 LONG WGS

TABLE 5 (CONT)

GEOMETRIC ALTITUDE FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CELSIUS	RELATIVE HUMIDITY PERCENT	DENSITY GRAMS PER CUBIC METER	SPEED OF SOUND METERS PER SECOND	WIND DATA DIRECTION DEGREES TRUE SPEED KNOTS	INDEX OF REFRACTION
3420220014	50.0	-55.0	101.1	504.4	292.8	10.2	1.000023
3420220014	50.0	-55.0	98.6	504.5	293.7	8.4	1.000022
3420220014	50.0	-55.0	96.2	504.6	294.1	6.6	1.000021
3420220014	50.0	-55.0	93.8	504.6	294.4	5.1	1.000021
3420220014	50.0	-55.0	91.5	504.6	295.3	4.8	1.000020
3420220014	50.0	-55.0	89.3	504.7	296.7	5.9	1.000020
3420220014	50.0	-55.0	87.1	504.7	297.5	7.1	1.000019
3420220014	50.0	-55.0	85.0	504.7			1.000019
3420220014	50.0	-55.0	82.9	504.8			1.000018
3420220014	50.0	-55.0	80.8	505.0			1.000018
3420220014	50.0	-55.0	78.8	505.2			1.000018
3420220014	50.0	-55.0	76.8	505.5			1.000017

STATION ALTITUDE 4010.00 FEET MSL  
 8 DEC. 79  
 ASCENSION NO. 14

MANDATORY LEVELS  
 3420220014  
 12X 30

GEODETIC COORDINATES  
 32.00497 LAT DEG  
 106.49714 LONG DEG

TABLE 6

PRESSURE GEOPOTENTIAL		TEMPERATURE		REL. HUM.		WIND DATA	
MILLIBARS	FEET	AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE	PERCENT	DIRECTION DEGREES(TN)	SPEED KNOTS	
850.0	5157.	9.1	-2.5	44.	171.2	3.9	
800.0	6002.	9.1	-4.4	38.	197.8	7.9	
750.0	6550.	6.7	-6.3	39.	243.3	12.0	
700.0	10376.	3.0	-9.0	39.	260.2	11.0	
650.0	12359.	.9	-7.8	52.	257.7	14.4	
600.0	14453.	-2.8	-13.6	43.	240.0	15.8	
550.0	16791.	-6.9	-19.2	37.	259.0	17.9	
500.0	19117.	-12.6	-25.3	32.	200.3	17.6	
450.0	21713.	-17.8	-30.8	31.	313.8	8.9	
400.0	24523.	-25.1	-37.2	31.	307.6	12.2	
350.0	27717.	-32.0	-44.2	31.	304.5	15.2	
300.0	31209.	-42.2			319.0	14.8	
250.0	35164.	-51.8			313.8	15.6	
200.0	39825.	-58.9			276.3	32.9	
175.0	42565.	-60.4			274.2	36.2	
150.0	45790.	-61.5			272.2	32.2	
125.0	49408.	-62.4			260.2	22.7	
100.0	53474.	-67.3			252.6	20.1	
50.0	56542.	-65.3			271.2	13.6	
70.0	60976.	-67.4			300.7	6.2	
60.0	64377.	-63.2			205.3	9.2	
50.0	67753.	-63.0					

\*\* AT LEAST ONE ASSURED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.